


# RKP56PKB-1/TXL

## Supply Cable - M12 Power – Connection Cable



### Technical data

|                           |                                                              |
|---------------------------|--------------------------------------------------------------|
| Type                      | RKP56PKB-1/TXL                                               |
| ID                        | 100003295                                                    |
| Connector A               | Female, M12 × 1, Straight, K-coded                           |
| Number of pins            | 4+PE                                                         |
| Contacts                  | Copper-nickel, CuNi, Gold-plated                             |
| Contact carriers          | Plastic, PBT GF, Black                                       |
| Connector body            | Plastic, TPE, Black                                          |
| Coupling nut/screw        | Brass, CuZn, Nickel-plated                                   |
| Seal                      | Plastic, FPM/FKM                                             |
| Tightening torque (range) | 0.5 ... 0.6 Nm<br>(observe max. torque of mating connector!) |
| Mechanical lifespan       | > 100 Mating cycles                                          |
| Pollution degree          | 3                                                            |
| Protection class          | IP65, IP67, IP69K, Only in screwed condition                 |


|                                           |                           |
|-------------------------------------------|---------------------------|
| <b>Cable</b>                              |                           |
| Cable diameter                            | Ø 8 mm ±0.20              |
| Cable length                              | 1 m                       |
| Cable jacket                              | PUR, Black                |
| Core insulation                           | PP                        |
| Core cross-section                        | 5 x 1.5 mm <sup>2</sup>   |
| Core colors                               | BK1, BK2, BK3, BK4, GN/YE |
| <b>Electrical properties at +20 °C</b>    |                           |
| Rated voltage                             | 600 V                     |
| Current                                   | 16 A                      |
| <b>Mechanical and chemical properties</b> |                           |
| Bending radius (stationary installation)  | ≥ 4 x Ø                   |

### Features



- M12 female connector, K-coded, straight, 5-pin (4+PE)
- Jacket material: PUR
- Jacket color: black
- Highly resistant to oils, coolants, lubricants and emulsions
- Suitable for use in drag chains
- Resistant to vibrations and shocks
- Flame retardant
- Halogen-free
- RoHS compliant
- UL approval
- Protection class: IP65, IP67, IP69K
- Cable length: 1.0 m


### Cable Cross-Section




### Contact assignment

Technical data

|                                    |                 |
|------------------------------------|-----------------|
| Bending radius (flexible use)      | ≥ 7 x Ø         |
| Bending cycles                     | ≥ 10 million    |
| Admissible acceleration            | max. 5 m/s²     |
| Admissible travel path, horizontal | 5 m (at 5 m/s²) |
| Torsional stress                   | ± 30 °/m        |
| Ambient temperature (fixed)        | -40...+80 °C    |
| Ambient temperature (mobile)       | -30...+80 °C    |
| Ambient temperature (drag chain)   | -20...+60 °C    |
| Qualified for drag chain use       | yes             |
| Halogen-free                       | yes             |
| Oil-resistant                      | yes             |
| Flame-retardant                    | yes             |
| Approvals                          | cULus           |



Circuit Diagram



Derating Curve



Accessories

| Dimension drawing | Type                   | ID        |                                                                                                                                                                                                                        |
|-------------------|------------------------|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                   | LABEL-HOLDER-FLEX-PVC  | 100048170 | PVC label holder for identification of extension cables (TEL/TXL product series); for cable diameters: min. 5 mm; dimensions 4 × 18 mm; delivery unit: 50 pcs. per package                                             |
|                   | VH2-M12K-M5-2F5        | 100028585 | Small h-splitter, M12 Power, K-coded, 4-pin + PE                                                                                                                                                                       |
|                   | FW-ERSPM0514-PK-S-0813 | 100008138 | Field-wireable male connector, M12 Power, straight, 4-pin + PE, screw terminal connection, cable feedthrough 8.0 to 13 mm, core cross-section/terminal capacity 1.5 to 2.5 mm², plastic housing, metal retaining screw |
|                   | VH3-M12K-M5-3F5        | 100028590 | Large H-splitter, M12 Power, K-coded, 4-pin + PE                                                                                                                                                                       |
|                   | VT2-M12K-M5-2F5        | 100029331 | T-splitter, M12 Power, K-coded, 4-pin + PE                                                                                                                                                                             |