



DWE-10000-135-195-IOL32B-H1141

Draw-Wire




Technical data

Type	DWE-10000-135-195-IOL32B-H1141
ID	100049440
Measuring principle	Magnetic
General data	
Measuring range	10000 mm
Linearity deviation	≤ 0.05 %
Electrical data	
Operating voltage U_B	18...30 VDC
No-load current	≤ 40 mA
Short-circuit protection	yes
Wire break/reverse polarity protection	yes
Communication protocol	IO-Link
Output function	4-pin
IO-Link	
IO-Link specification	V 1.1
Programming	FDT/DTM
Mechanical data	
Design	Draw Wire
Housing material	Titanium anodized aluminium
Encoder housing material	Die-cast zinc
min. extension force	8.7 N
max. extension force	16.9 N
max. extension speed	6 m/s
Pull acceleration max.	80 m/s ²
wire material	Stainless steel
Electrical connection	Connector, M12 × 1

Features

- Highly dynamic draw-wire sensor
- With permanently installed IO-Link encoder REM-E-195T10C-IOL32B-H1141
- Measuring principle: magnetic
- Sensor protection class IP65
- -20...+85 °C
- 18...30 VDC
- M12 × 1 connector, 4-pin

Wiring diagram



Technical data

Environmental conditions	
Ambient temperature	-20...+85 °C
Protection class	IP65

Accessories

RDR-1	1544753
-------	---------

Deflection roller for aluminium draw-wire sensors

