


Photoelectric Sensor


Photoelectric Sensor for Plastic Fibers

D10DPFPQ5



- M12 × 1 cable with male end, 150 mm, 6-pin
- Teach-in programming
- Response time, adjustable
- Red visible light
- Operating voltage 12...24 VDC
- Optical sensitivity, adjustable
- Switch-off delay (0...100 ms)

Wiring Diagram



Functional principle

Glass or fibre optic sensors are the optimum choice for high temperature or space restricted applications. Fibre optics transfer the light from the sensor to a remote object. Individual fibre optics are used for opposed mode sensing, whereas bifurcated fibre optics are suited for diffuse mode operation.

Type	D10DPFPQ5
ID	3066314
Optical data	
Function	Fiber optic sensor
Operating mode	Plastic fiber
Fiber-optic type	plastic
Light type	Red
Wavelength	680 nm
Electrical data	
Operating voltage U_s	12...24 VDC
Residual ripple	< 10 % U_s
No-load current I_o	≤ 65 mA
Short-circuit protection	yes
Reverse polarity protection	yes
Output function	2 x NO contact, PNP
Switching frequency	10 kHz
Readiness delay	≤ 1000 ms
Response time typical	< 0.05 ms
Setting option	Push Button Remote Teach
Mechanical data	
Design	Rectangular, D10
Housing material	Plastic, Thermoplastic material
Electrical connection	Cable with connector, M12 × 1, 0.15 m, PVC
Number of cores	6
Core cross-section	0.34 mm ²
Ambient temperature	-10...+55 °C
Relative humidity	0...90%
Protection class	IP50
Special features	
keep/defer	
Power-on indication	LED, Green
Switching state	LED, Yellow
Excess gain indication	Single Digital Display

Tests/approvals


Approvals

CE, cURus

Accessories

Type code	Ident no.		Dimension drawing
SMBR55F01	3067104	Mounting panel, PBT, black, for R55F series, wall mounting	
SMBR55FRA	3058809	Mounting bracket, 19-ga. stainless steel, for D10, DF-G1 and R55F series, lateral wall mounting	
DIN-35-70	3026604	DIN rail, width 35 mm, length 70 mm	
DIN-35-105	3030470	DIN rail, width 35 mm, length 105 mm	
DIN-35-140	3026605	DIN rail, width 35 mm, length 140 mm	

Function accessories

Type code	Ident no.		Dimension drawing
PIT46U	3026034	Plastic fiber-optic sensor, operating mode: Opposed mode, threaded sleeve M3 x 0.5 mm, field wireable wire without end tip, polyethylene sheath, ambient temperatures -30 °C...+70 °C	 2000 11 3 $\varnothing 2,2$ M4 x 0,7 M2,5 x 0,45 Nickel plated brass $\varnothing 1$ fibre
PBT46U	3025967	Plastic fiber-optic sensor, operating mode: Diffuse mode, threaded sleeve M3 x 0.75 mm, field wireable wire without end tip, polyethylene sheath, ambient temperatures -30 °C...+70 °C	

