

# Barcode Reader — Image Sensor IVU2PTBW25



|                                  |                                                        |
|----------------------------------|--------------------------------------------------------|
| Type                             | IVU2PTBW25                                             |
| ID                               | 3090878                                                |
| <b>Camera data</b>               |                                                        |
| Function                         | Barcode reader - image sensor                          |
| Resolution                       | 752 × 480 pixels                                       |
| Light type                       | White                                                  |
| Brennweite                       | 12 mm                                                  |
| Special features                 | Wash down                                              |
| <b>Electrical data</b>           |                                                        |
| Operating voltage $U_s$          | 10...30 VDC                                            |
| DC rated operating current $I_s$ | ≤ 1000 mA                                              |
| Communication protocol           | EtherNet/IP<br>Modbus TCP<br>PCCC<br>PROFINET<br>RS232 |
| <b>Mechanical data</b>           |                                                        |
| Design                           | Rectangular, iVu PLUS                                  |
| Housing material                 | Plastic, Thermoplastic material, Black                 |
| Window material                  | Acrylic, clear                                         |
| Electrical connection            | Connector, M12 × 1, 12-wire                            |
| Display                          | Integriert                                             |
| Ambient temperature              | 0...+50 °C                                             |
| Protection class                 | IP67                                                   |
| <b>Tests/approvals</b>           |                                                        |
| Approvals                        | CE                                                     |

- Second iVu generation
- Internal memory for 30 inspections
- 1/3" CMOS, 752x480 pixels
- Integrated ring light: White
- Protection class IP67
- External strobe output + 5 VDC
- External trigger input
- Lens, 25mm, M12x1
- Display: Integrated 65.5 mm LCD color display, 320 x 240 transreflective
- Operating voltage 10...30 VDC
- M12 x 1 male, 12-pin
- Three PNP/NPN switching outputs, selectable via software
- USB 2.0 host: M8 female, 4-pin
- Ethernet via M8 x 1 male, 4-pin
- Industrial Ethernet: PROFINET, EtherNet/IP, Modbus/TCP, PCCC

## Wiring Diagram

|             |                       |
|-------------|-----------------------|
| 1 WH        | Output 1              |
| 2 BN        | 10...30 VDC           |
| 3 GN        | Output 2              |
| 4 YE        | Strobe out 5 VDC only |
| 5 GY        | Remote teach          |
| 6 PK        | Ext. trigger          |
| 7 BU        | Common                |
| 8 RD        | Ready                 |
| 9 OG        | Output 3              |
| 10 BU light | RS-232 TX             |
| 11 BK       | RS-232 signal ground  |
| 12 VT       | RS-232 RX             |

## Functional principle

The second generation of the iVu-Plus offers the user advanced features and even more options in the selection of the inspections. The sensor is equipped with the same hous-

ing and offers the same intuitive user interface and functionality of the previous iVu generation. The barcode reader consists of a camera and an integrated light (except the IVU2TBX version) able to scan up to 10 different barcodes and to transmit the data via the RS232 interface. A selection can be configured for certain barcode types such as DataMatrix (ECC 200) and a number of linear codes such as Code128, Code39, CODABAR, Interleaved 2 of 5, EAN13, EAN8, UPCE, Postnet, IMB and Pharmacode. The possibility to select between coarse and fine resolution is available with the new generation. Sensor configuration via PC is not required! Log files and firmware updates can be transmitted via the USB interface.

## Accessories

| Type code | Ident no. |                                                       | Dimension drawing |
|-----------|-----------|-------------------------------------------------------|-------------------|
| SMBIVURAR | 3082547   | Brackets for mounting on right side                   |                   |
| SMBIVURAL | 3082546   | Brackets for mounting on left side                    |                   |
| SMBIVUU   | 3082549   | U-bracket for base mounting (incl. SMBIVUB baseplate) |                   |