



## LED Linear Light In the Metal Housing WLS28-2XBR-1130XQ



- Color 1: blue (100% light intensity)
- Color 2: red (100% light intensity)
- 2-color linear light
- M12 x 1 male, straight, 4-pin
- SMBWLS28RA mounting bracket included in delivery

## Wiring Diagram



Туре	WLS28-2XBR-1130XQ
ID	3804785
	0001100
Signal and display data	
Purpose	LED work light
Function	Linear light
Light type	Blue
	Red
Aperture angle degree	60 °
Beam angle	wide beam 40-80°
LED service life (L70)	50000 h
Dimmable	Yes
Features of color 1	Blue, Permanently on, 100 %, 320 lm
Features of color 2	Red, Permanently on, 100 %, 440 lm
Electrical data	
Operating voltage U <sub>B</sub>	1230 VDC
DC rated operating current I <sub>e</sub>	≤ 3040 mA
Input power	36.48 W
Mechanical data	
Cascadable	No
Design	Rectangular, WLS28-2
Housing material	Metal, AL
Window material	Polycarbonate, clear
Electrical connection	Connector, M12 × 1, PVC
Number of cores	4
Ambient temperature	-40+70 °C
Storage temperature	-40+70 °C
Relative humidity	090%
Protection class	IP50
Tests/approvals	
Approvals	CE, UL
• •	, -

## **Functional principle**

The energy-efficient LED work lights are ideally suited for industrial applications. The color temperature is between 4,700 and 5,300 Kelvin (cool white). Depending on the model, the luminous flux is 475 or 1900 lumen. Some work lights are switched on/off via supply power (10...30 VDC) and some types by means of a button directly at the LED lamp. In addition, the LED can be switched to second color by activating a high signal on PIN 4, or for the variants with a switch by means of a further switch position. This additional color can be selected with either 100, 50 or 33% light intensity. Cascadable variants are also available. Variants with a clear or diffuse plastic windows, as well as with an aperture angle of



## **Accessories**

Type code	Ident no.		Dimension drawing
SMBWLSMAG	3019574	Magnetic fixture for mounting work lights and sensors, 2 pieces	o 5,1 o 51,8
SMBWLS28RA	3015764	Mounting bracket, angled, metal, for WLS28 work lights, 5 mm drill holes, screw set included	0 3 0 24 0 15,3 0 5 18 17, 25 19 19
SMBWLS28SP	3088063	Snap bracket for mounting WLS28 work lights	28.9 17.8 10.7.1 35