








Wskaźnik napięcia zasilania	LED, zielony
Wskaźnik stanu przełączenia	LED, Żółty
Wskazanie błędu	LED, zielony, Flashing
Wskaźnik wzmacnienia	LED, czerwony, miganie
Testy/aprobaty	
Certyfikaty	CE



Akcesoria montażowe

Typ	Nr kat.		Rysunek wymiarowy
SMBQS30Y	3002811	Protective housing, stainless steel, for QS30 series	
SMBQS30YL	3072741	Protective housing with safety glass panel, stainless steel, for QS30 series	
SMB30A	3032723	Uchwyt montażowy, prostopadłościenny, stal nierdzewna, dla czujników z gwintem 30mm	
SMBQS30L	3002809	Mounting bracket, stainless steel, for QS30 series	
SMB30MM	3027162	Uchwyt montażowy, prostopadłościenny, stal nierdzewna, dla czujników z gwintem 30 mm, szerokie otwory dla dokładnego wyrównania	

Akcesoria montażowe

Typ	Nr kat.		Rysunek wymiarowy
SMB30SC	3052521	Uchwyt montażowy, czarny PBT, dla czujników z gwintem 30 mm, obrotowy	 Technical drawing of the SMB30SC mounting bracket. The drawing shows a 3D perspective view of the component. Key dimensions are labeled: 12.7 (width of the top flange), 66.5 (total width), 58.7 (height of the main body), 29 (width of the base), 50.8 (width of the base flange), and M30 x 1.5 (thread specification for the mounting hole). The component is shown in a grey color.